

2 Megapixel Mini Dome IP Camera

6533

Channel Vision's 6533 IP mini dome camera offers superior image quality with a 2 megapixel CMOS sensor and has the ability to capture images up to 1920 x 1080 pixels. The 6533 is equipped with a built-in web server that allows high quality videos to be viewed in real-time using the Internet Explorer browser. The application to view the 6533 on an Android, iPhone and iPad is available from the respective store. This camera contains 36 Camera CMS to allow users to view all of their cameras in the same window from anywhere in the world.



FEATURES

Power over Ethernet

High definition 1080p at 30 FPS

Digital Wide Dynamic Range

Micro SD card

Vandal Proof Dome

SPECIFICATIONS*

*Specifications subject to change.

Hardware

CPU: Arm 9, 32 bit RISC

RAM: 128MB

Flash: 16MB

Image Sensor: 1/2.7" CMOS Sensor

Sensitivity: Color: 0.1 Lux (AGC On)

Lens Type: 2.8mm

Power Over Ethernet: Yes, 48V power consumption, max 3.36 Watts

Power: 12vDC max 2.40 Watts

Operating Temperature: 14 °F-113 ° (-10 °C - 45 °C)

Dimensions: 3.15" in Diameter x 2.64" Height

Field of View: 111.10 ° (H) x 65.10 ° (V)

Weight: 11.99 Ounces

Network

Ethernet: 10/100 Base-T

Network Protocol: HTTP, HTTPS, SNMP, QoS/DSCP, Access list, IEEE, 802.1X, RTSP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour & ONVIF

Live Viewing

OS: Windows XP, 7, 8, or Macintosh version 10.6 or newer

Browser: Microsoft IE 6.0 or newer, Safari, Firefox & Chrome

Suggested Hardware: Intel Dual Core 1.66G, RAM: 1024MB, Graphic card: 128MB (Windows)

System

Video Resolution: 1920x1080 (Max), 1280x720, 640x480, 320x240, 126x144

Video Adjustments: Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Shutter Speed adjustable, Sense-Up, D-WDR, Flip, Mirror, Noise reduction, DNR