

M.S.D.S. Label

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ESL SMOKE IN A CAN! # - MSDSSM200
MANUFACTURED FOR: GE SECURITY INC. PRODUCT - SM200
12345 SW LEVETON DR, TUALATIN, OR. 97062 PHONE: (503)692-4052

1. INGREDIENTS	CAS#	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
1,2,3-Propanetriol	56-81-5	10mg/m3	(mist)	NA	1-5
Ethanol	64-17-5	1000ppm	1000ppm		25-35
Propane	74-98-6	2500ppm	1000ppm		25-35
Isobutane	75-28-5	NA	NA	1000ppm	25-35

2. PHYSICAL DATA: (without propellant)

Specific Gravity: 0.81 Vapor Pressure: ND
% Volatile: 97
Boiling Point: 172° F (initial) Evaporation Rate: NA
Freezing Point ND Vapor Density: 1.6 (air=1) est.
Appearance and Odor: ph: NA
Colorless liquid, alcohol odor. Solubility: Appreciable in water.

3. FIRE AND EXPLOSION DATA: (without propellant)

Flashpoint: 56° F Method :TCC
Flammable Limits: est. LEL 3.53 UEL: 21.2
Extinguishing Media: Water spray, Dry chemical, CO2
Alcohol foam

Unusual Hazards: Vapors may cause a flash fire or ignite
explosively. Prevent build-up of vapors.

4. REACTIVITY AND STABILITY

Stability: Stable
Hazardous decomposition products: Acrolein
Materials to avoid: Strong oxidizing agents.

5. PROTECTION INFORMATION

Ventilation: Good general ventilation should be used.
Respiratory: Use self contained breathing apparatus if
accumulation of vapors is suspected.

Gloves: Solvent resistant Eye & Face: Safety glasses
Other Protective Equipment: Not normally required with aerosol
product usage.

6. HEALTH HAZARD DATA

Primary Routes of Entry: Skin, Inhalation

Signs and Symptoms of Exposure**1. Acute Overexposure:**

Inhalation: High vapor concentrations may cause drowsiness & irritation.
Eyes: High vapor concentrations may cause irritation.
Skin: Irritation & drying.

2. Chronic overexposure: Prolonged or repeated skin contact may
cause drying, cracking or irritation.

Medical Conditions Generally Aggravated by Exposure: None known.

Chemical Listed as Carcinogen or Potential Carcinogen
National Toxicology Program: No IARC Monographs: No OSHA: No

Emergency and First Aid Procedures: (if symptoms persist,
call a physician)

1. Inhalation: Move to fresh air. Treat symptomatically.
Get medical attention if symptoms persist.

2. Eyes: Immediately flush with plenty of water for at least
15 minutes. Get medical attention.

3. Skin: Wash with soap and water. Get medical attention if symp-
toms occur.

4. Ingestion: Call a physician immediately. Induce vomiting
as directed by physician.

7. SPILL OR LEAK PROCEDURES

Precautions to be taken in Handling and Storage: Keep container
tightly closed and store in a well-ventilated area.

Steps to be taken in case Material is released or spilled. Eliminate all
ignition sources. Absorb material with vermiculite or other inert mate-
rial, then place in a container for chemical waste.

Waste Disposal: All used and unused Product should be disposed of
in conformance with local, state and federal regulations.

8. SPECIAL PRECAUTIONS AND USE DIRECTIONS:

Aerosol cans may explode if heated above 120° F. Use this product in
areas of good ventilation. Vapors are heavier than air and will collect
in low areas.

9. NFPA HAZARD RATINGS Health: 2 Flammability: 4 Reactivity: 0

10. SARA Information

This product contains NO chemicals that are subject to release
reporting under section 313 of SARA Title III.

24 HOUR EMERGENCY INFORMATION

CALL: CHEMTREC 800-424-9300

PREPARED BY: L.J. EGGER, GE SECURITY INC. ORIGINAL DATE OR DATE OF REVISION: 2/18/04

Please do not remove the label from this can until the can is completely empty.