

Comparison: VG-1C12BQ vs. VG-1C12AQ

	VG-1C12BQ *NEW*	VG-1C12AQ
Model		
Connector In	Gold-Plated BNC Male with 6" Pigtail	Gold-Plated BNC Male
Connector Out	Gold-Plated BNC Female with 6" Pigtail	Gold-Plated BNC Female
Dimensions	2 ⁷ / ₈ " x 1 ³ / ₃₂ " x 3 ³ / ₄ " (73 x 28 x 19 mm)	2 ³ / ₁₆ " x 1 ⁷ / ₃₂ " x 1" (55 x 31 x 26 mm)
Weight	2.3-oz (65g)	1.8-oz (51g)
Bandwidth	Video DC to 8Mhz	Video DC to 8Mhz
Maximum input	1.0Vp-p	1.0Vp-p
Impedance	75 Ω (BNC-to-BNC)	75 Ω (BNC-to-BNC)
Insertion loss	<0.5dB	<0.5dB
Frequency response	0-3dB at 10MHz	0-3dB at 10MHz
Isolation voltage	600VDC (min.)	600VDC (min.)
Insulation resistance	100MΩ	100MΩ
Transient voltage suppressors	12 Vrms	12 Vrms
Material	ABS Black	ABS Black
Operating temperature	32° ~ 131°F (0° ~ 55° C)	32° ~ 131°F (0° ~ 55° C)

SECO-LARM

16842 Millikan Ave • Irvine, CA 92606

Tel: 949-261-2999 / 800-662-0800 • Fax: 949-261-7326

sales@seco-larm.com • www.seco-larm.com



Copyright 2012 © SECO-LARM U.S.A, Inc. All rights reserved.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM CRIMEBUSTER® CBA SLI

GroundLoopIsolators.docx