


## 1000 TVL Indoor/Outdoor IR Vandal Resistant Dome with True WDR

**HT5940K**

2.8-12mm auto iris varifocal lens, dark grey housing



Shown with included paintable, snap-on Chameleon Cover™

### Features

- 1/3" 1.3MP Sony Sensor
- 1000 TV lines highest resolution in analog
- True WDR functionality
- Chameleon Cover™: snaps on and can be painted to match any décor!\*
- 12VDC & 24VAC dual voltage operation
- 3-axis wall and ceiling mount
- Vandal / tamper resistant operation
- IP67 compliant
- 5 year warranty

### Specifications

|                               |                                                        |                                 |                                                                     |
|-------------------------------|--------------------------------------------------------|---------------------------------|---------------------------------------------------------------------|
| Image Sensor .....            | 1/3" 1.3MP Sony Sensor                                 | Brightness.....                 | 0 - 20 (level adjustable)                                           |
| Resolution.....               | 1000 TV lines                                          | AGC.....                        | 0 - 20 (level adjustable)                                           |
| Minimum Illumination.....     | 0 lux (IR LEDs on)                                     | Smart-IR .....                  | 0 - 20 (level adjustable)                                           |
| Effective Pixels .....        | 1305 (H) x 1049 (V)                                    | Sense-Up.....                   | (x2 - x32)                                                          |
| Total Pixels .....            | 1312 (H) x 1069 (V)                                    | Motion Tracking.....            | On / Off                                                            |
| TV System .....               | NTSC                                                   | Motion Detection.....           | On / Off (4 zones)                                                  |
| Scanning System.....          | Progressive                                            | Privacy.....                    | On / Off (16 zones)                                                 |
| Number IR LEDs .....          | 18                                                     | Mirror / V-Flip .....           | On / Off                                                            |
| IR Range .....                | Up to 66 ft. (depending on scene reflection)           | Sharpness .....                 | 0 - 15 (level adjustable)                                           |
| IR LED Wavelength.....        | 850nm                                                  | Lens Shading Compensation ..... | On / Off                                                            |
| S/N Ratio .....               | More than 50dB                                         | 3DNR.....                       | Off / Low / Middle / High                                           |
| Frame Rate.....               | Max 50P/60P                                            | Defog.....                      | On (Auto / Manual) / Off                                            |
| Video Output.....             | 1.0Vp-p / 75 ohms                                      | DIS.....                        | On / Off                                                            |
| Lens.....                     | DC / Manual                                            | Power Supply .....              | 12VDC / 24VAC dual voltage operation<br>(power supply not included) |
| Electronic Shutter Speed..... | Auto / Manual<br>(1/60 sec. - 1/60,000 sec.) / Flicker | Power Consumption .....         | 12VDC, 450mA / 24VAC, 190mA                                         |
| WDR.....                      | On (Low / Middle / High) / Off                         | Operating Temperature.....      | -4° F - 140° F                                                      |
| Digital WDR.....              | On (Low / Middle / High) / Off                         | Dimensions.....                 | 4.72" (Dia.) x 3.35" (H)                                            |
| Day/Night.....                | Color / BW / Auto / Ext                                | Weight .....                    | 2.2 lbs.                                                            |
| White Balance .....           | Auto / Auto Ext / AWC - SET / Manual                   |                                 |                                                                     |

### Optional Accessories



**INTPM**  
Pendant Mount  
(use with 59PLATE  
and CVCJBD)



**INTWM**  
Wall Mount  
(use with 59PLATE  
and CVCJBD)



**CVCJBD**  
Dome Camera  
Junction Box  
(use with 59PLATE)



**59PLATE**  
Adaptor Plate



**PSW4**  
24VAC  
Power Supply



**PSW5**  
12VDC  
Power Supply



\*Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/11/15