

VistaCam 702

Indoor Wi-Fi Camera
with 2-way audio



Key features

This indoor, high definition, Wi-Fi camera is compact, easy to install, and ideal for any home or small business security system. With a 1080p HD picture, built-in infrared illumination up to 16 feet, and two-way audio that lets you speak with the people you see, you can keep an eye on your living room, nursery, entryway, and more day or night.

The VistaCam 701 also doubles as a motion detector, enabling useful home automation features such as turning on a hallway light to 30% when motion is detected after dark. Whether placed on a flat surface or mounted on a wall, its sleek design blends seamlessly with any decor.



Indoor camera with full HD, 1080p resolution



Two-way talk lets you communicate with people in your home



Infrared night vision keeps watch when you're asleep



16GB microSD card included



Motion activated recording



Magnetic base for easy installation

Specs

Video

Recording quality

1080p HD (1920x1080) at 30 fps. 1080p (1920x1080), (704x480), (528x320)

Compression

H.264 Main Profile, M-JPEG Video

Streaming

Mobile Phone 3GPP Compatible

Video backup storage

16 GB included. Up to 128 GB

Dynamic range

WDR

Image settings

Auto adjust Exposure, Contrast, Brightness, Sharpness, Flip

Camera

Image sensor

2 megapixels; 1/2.7 HD
Progressive Scan CMOS

Minimum illumination

0 Lux (with IR LED)

Lens

Fixed Focus Lens, F2.0 Aperture

Pan-Tilt-Zoom

No

Motion Detection

Mobile Phone 3GPP Compatible

Field of View

115° Horizontal, 135° Diagonal

Camera

Night Vision

IR cut filter with auto switch. Manual mode optional. 16ft (5m) Range. 25 feet (7.5m) Range. Light Sensor

Image settings

Auto adjust Exposure, Contrast, Brightness, Sharpness, Flip

Audio

Microphone

36 dB ± 3dB
G.711

Speaker

Yes

2 Way audio

Yes

Hardware

Processor

HI3518EV200, 540MHz

Memory

16MB NOR Flash
64MB DDR2 RAM Memory

Lights

1 front facing multi color LED

Buttons

Reset

Expandable storage

Micro SD: 16GB installed. Up to 128GB

Connectors

Micro USB Port (Power Supply)

Network connections

Wi-Fi	Protocols	Ethernet
802.11b/g/n @ 2.4GHz (WEP, WPA, WPA2 encryption supported)	DHCP, HTTP, NTP, RTSP, ISAPI	No
WPS (Wi-Fi Protected Setup)		
-		

Power

Input	Output
AC Power Adapter 100-240 VAC, 50-60 Hz Indoor power outlet required	DC 5V/1A

Size

Height	Width	Depth
4,3in (110mm)	2.28in (58mm)	1.49in (38mm)

Storage environment

Temperature

14° to 113°F (-10° to 45°C)

Humidity

95% or less (non-condensing)

Operating environment

Usage

Indoor

Weather resistance

No

Temperature

14° to 113°F (-10° to 45°C)

Humidity

95% or less (non-condensing)

Certifications



What's in the box

VC702
Power supply with 10-foot cable

Metal mounting plate
Adhesive sticker

Quick Start Guide

Details

