



zipato® ZIPATILE ALL IN ONE

One device = complete home control and automation



SECURITY ALARM

- Motion sensor
- Noise sensor
- Shock sensor
- Touch keypad
- Multi-sound alarm siren
- Photo and video messages
- 24/7 central monitoring
- Remote control with smartphone



HOME AUTOMATION

- Remote control with smartphone
- Online rule creator
- Scene manager
- Room manager
- Z-Wave, ZigBee, Nest, Philips Hue, Sonos, Bluetooth...



ELDERLY CARE

- Motion sensor
- Noise detector
- Automatic check calls
- Panic button with auto call
- Sound reminders
- Video and voice calls



WALL PANEL

- Room temperature
- Room illuminance
- Room humidity
- Weather forecast
- Sticky notes
- News stream
- Photo frame
- Email, Skype, browser
- Multimedia control
- Scene controller with 6 buttons



THERMOSTAT

- Gas/floor heating
- Temperature meter
- Exterior temperature meter
- Air condition control
- Remote control with smartphone



INTERCOM

- SIP server client
- Door phone control
- Conference calls
- Video calls
- Dual-network IP connectivity
- Remote control with smartphone



IP CAMERA

- 2 megapixels
- Live video stream H.264
- Motion and scheduled recordings
- Remote control with smartphone



ZIPATILE

Zipatiles is the complete home control system in a form of a single device. It can easily be mounted on any wall, in any home. Featuring large number of built-in sensors and hardware modules, ZipaTile will replace numerous home devices such as security system, thermostat, automatic controller, IP camera, alarm siren or intercom, and bring them together in one, smart and beautiful device.



TECHNICAL SPECIFICATION

→ APPLICATIONS

Security System
Thermostat
Elderly Care System
Home Automation
Video Monitoring
Intercom
Room Controller

→ SYSTEM

ARM Cortex-A9, Quad-core 1.6GHz CPU
1024MB RAM
8192MB FLASH
Android 5 Lollipop

→ NETWORK

Wi-Fi 802.11 b/g/n
Ethernet (with optional adapter)
Bluetooth 4.0
Philips Hue
Sonos
Nest
Z-Wave+ (500 series)
ZigBee HA

→ SENSORS

Noise
Light
Humidity
Temperature
Motion
Shock

→ POWER

Power input: 5VDC
Power supply input: 100-240VAC, 50/60Hz
Power usage: <2W (Idle), 7W (Max.)
Backup battery: Li-Ion 3.7V 2000mAh

→ INPUT/OUTPUT

Touch sensitive 8" screen, 800x1280 px
6 programmable scene buttons
Dry output 230VAC, 1A (EU: 2x; US: 3x)
Dry input 12-24VDC (only EU version)
External temperature sensor (1-Wire DS18B20)
2MP video camera
Multi-sound alarm siren
SD card

Speaker 8Ω/1.5W
Microphone

→ ACCESSORIES

In-Wall power supply
Wall socket adapter
Wall holder
Screws
Table stand
Quick start guide

→ PHYSICAL DIMENSION

8.05(W) x 8.05 (H) x 0.55 (D) inches
205(W) x 205(H) x 14(D) millimeters

→ WEIGHT

Netto: 579g (20.4oz) Brutto: 1,121kg (39.54oz)

→ ENVIRONMENTAL

Operating temperature: 0°C to 40°C (32°F to 104°F)
Storage temperature: -25°C to 70°C (-13°F to 158°F)
Humidity: 5% to 95% non-condensing

→ REGULATION

Safety: UL power supply
CE, FCC, IC
ROHS, REACH

→ MODELS

zt.zwauzbee	Black	Australia
zt.zweuzbee.b	Black	United Kingdom
zt.zweuzbee.g	Black	Europe
zt.zwinzbee	Black	India
zt.zwiszbee	Black	Israel
zt.zwrzbee	Black	Russia
zt.zwuszbee	Black	United States
zt.zwauzbee.wht	White	Australia
zt.zweuzbee.b.wht	White	United Kingdom
zt.zweuzbee.g.wht	White	Europe
zt.zwinzbee.wht	White	India
zt.zwiszbee.wht	White	Israel
zt.zwrzbee.wht	White	Russia
zt.zwuszbee.wht	White	United States

→ WARRANTY

1 year standard